

**ООО "KMK завод"**  
**«Kaluga Plant of Metal Construction LTD»**

39, Komsomolskoy Roschi Street, Kaluga, 248010, Russian Federation  
Registration № 1104029000910

Kaluga

2017

To All interested  
persons

**LETTER OF INFORMATION**

ООО „ KMK завод” , being a manufacturer of metal furniture, informs  
You that „ Prooftools” Ltd., legal address: 38b Upes street, Rēzekne, Latvia, LV-  
4601, is a part of the dealers and can carry out the deliveries of products of ООО „  
KMK завод” in the countries of the European Union.

General Director



N.V. Zueva

## DRYING CABINET HOTBOX-2000, HOTBOX-2000N\*\*

Drying cabinet HOTBOX-2000 is used for drying humid and wet clothes and shoes. The cabinet is equipped with detachable mesh shelves, which allow rationally use the internal space of the cabinet (drying clothes with different lengths). The cabinets can be connected to the exhaust ventilation. For this purpose, a flange for connecting the corrugated pipe is located on the roof of the dryer.

Locking of the cabinet is "overlap" with the help of the right door with the mail lock and the currently available deadbolt.



## DRYING CABINET STRENGTHENED HOTBOX-2000B

Drying cabinet for flak jackets HOTBOX -2000B is used for drying humid and wet flak jackets in the amount of 10-12 pieces. Inside the cabinet are located mesh shelves that allow profitable use the internal space of the cabinet. HOTBOX- 2000B can be connected to the hood. Locking of the cabinet is "overlap" with the help of the right door with the mail lock and the currently available deadbolt.



### TECHNICAL DATA

Dimensions HxWxD, mm:	1805x800x512*
Weight, kg:	60
Supply voltage:	220B / 50 Hz
Rated input, W:	
el. motor:	60
heating element:	2000
Overheat protection:	yes
Drying modes:	till 40°C till 60°C airing
Timer:	4 hours manual
Sound pressure level, dB:	<55
Fan productivity, m <sup>3</sup> /h:	360
The length of the electric power cord, m:	2,5



\* - without flange for air extraction, the diameter of the 120 or 125



Approvals:



Certificate NO.3-159-196/2017

flange to connect the cabinet to the exhaust ventilation, mm:  
\*\* - N - made of stainless steel



Approvals:



Certificate NO.3-159-196/2017



## DRYING CABINET HOTBOX-2000/4

Drying cabinet HOTBOX-2000 is used for humid and wet clothes and shoes. The main of this drying cabinet is that it has 4 independent compartments. Each compartment closes his door. And can be locked with its own key. Inside cabinet are located removable mesh shelves that profitable use the internal space of the cabinet clothes of any length). HOTBOX-2000/4 can be connected to the hood.



### TECHNICAL DATA

Dimensions HxWxD, mm:	1810x800x510*
Weight, kg:	60
Supply voltage:	220B / 50Hz
Rated input, W:	
el. motor:	60
Heatin element:	2000
Overheat protection:	yes
Drying modes:	till 40°C till 60°C airing
Timer:	4 hours manual
Sound pressure level, dB:	<55
Fan productivity, m <sup>3</sup> /h:	360
The length of the electric power cord, m:	2,5

\* - without flange for air extraction, the diameter of the flange to connect the cabinet to the exhaust ventilation, mm:

120 or 125



Approvals:



Certificate NO.3-159-196/2017



## DRYING CABINET UNIVERSAL-2000

Drying cabinet UNIVERSAL-2000 is used for drying humid and wet clothes and shoes. The cabinet has two vertical division, is equipped with four rods for shoes and a mesh shelf for hats or gloves.

### TECHNICAL DATA

Dimensions HxWxD, mm:	2000x650x512
Weight, kg:	56
Supply voltage:	220B / 50Hz
Rated input, W:	
el. motor:	60
Heating element:	2000
Overheat protection:	yes
Drying modes:	till 40°C till 60°C airing
Timer:	4 hours manual
Sound pressure level, dB:	<55
Fan productivity, m³/h:	360
The length of the electric power cord, m:	2,5



Approvals:



Certificate NO.3-159-196/2017

**PROOF  
TOOLS**

## DRYING CABINET KIDBOX 5

Drying cabinet «KIDBOX 5» for 5 sets is used for drying humid and wet clothe, shoes, hats, gloves and etc. Cabinets consist of five separate sections. Designed specifically for kindergartens and other preschool institutions.

### TECHNICAL DATA

Dimensions HxWxD, mm:	1641x1524x373*
Weight, kg:	123
Supply voltage:	220B / 50Hz
Rated input, W:	
el. motor:	60
Heating element:	2000
Overheat protection:	yes
Drying modes:	till 40°C till 60°C airing
Timer:	4 hours manual
Sound pressure level, dB:	<55
Fan productivity, m <sup>3</sup> /h:	360
The length of the electric power cord, m:	2,5
The number of sections, PCs.:	5
The number of shelves in a section, PCs.:	2
Number of vertical partitions, PCs.:	4
Distributed load on the shelf, kg:	max 10

\* - without flange for air extraction, the diameter of the flange to connect the cabinet to the exhaust ventilation, mm:

120 or 125



Approvals:



Certificate NO.3-159-196/2017

**PROOF  
TOOLS**

## DRYING CABINET RANGER 8

Drying cabinet «RANGER 8» for 8 sets is used for drying wet clothes, linen, also for various of sports uniforms and equipment. Cabinets consist of two sections. The first two-door for drying clothes, is equipped with rod for hangers and shelf for hats. The second section is for drying shoes and is equipped with special rods for hanging and drying shoes.



## DRYING CABINET STRENGTHENED RANGER 8B

Drying cabinet «RANGER 8B» for 8 sets is used for drying wet flak jackets and shoes. Cabinets consist of two sections. The first two-door for drying flak jackets, equipped with two rods for hanging. The second section is for drying shoes and is equipped with special rods for hanging and drying shoes.



### TECHNICAL DATA

Dimensions HxWxD, mm:	1881x1804x624
Compartment for drying clothes, inside dimensions: HxWxD, mm:	1830x1194x558
Weight, kg:	176
Supply voltage:	220B / 50Hz
Rated input, W:	
el. motor:	60
Heating element:	3000
The length of the electric power cord, m:	2,5



Approvals:



Certificate NO.3-159-196/2017

**PROOF  
TOOLS**

## DRYING CABINETS HOTSTORM

Drying cabinet «Hotstorm» is used for drying wet clothes, linen, also for various of sports uniforms and equipment. Cabinets consist of three sections for hanging clothes. The cabinets can be connected to the exhaust ventilation. For this purpose, a flange for connecting the corrugated pipe is located on the roof of the dryer.

In the concept of drying cabinet added sensor humidity control, control of the drying process is carried out using the software of the controller that will significantly expand the functionality of the product and use the individual settings of the drying process given the volume of cabinet and type of the dried fabrics.

The built-in timer with continuous adjustment allows for drying modes in time and delayed start of programs.

For the safe usage there are additional functions: shutting off the heating element when the door is opened, cooling of the heating element after switching off the cabinet and ending the program execution, mode "emergency stop" in case of overheating and burnout of the heating element every 2 seconds.

The Cabinet has ergonomic control panel with LCD screen and touch buttons.

Control the heating element using low voltage circuits allows use drying cabinet under reduced voltage in the supply circuit (for example, country houses, garages, etc.)



### TECHNICAL DATA

Dimensions HxWxD, mm:	1800x600x495
Weight, kg:	52
Supply voltage:	220B / 50Hz
Rated input, W:	
el. motor:	60
Heating element:	2000
Overheat protection:	yes
Drying programs:	the maximum dry normal dry wet/humid heated cold dry airing
Sound pressure level, dB:	<55
Fan productivity, m <sup>3</sup> /h:	360
The length of the electric power cord, m:	2,5
The number of sections, pcs.:	5
The number of shelves in a section, pcs.:	2
Number of vertical partitions, pcs.:	4



Approvals:



Certificate NO.3-159-196/2017

Distributed load on the shelf, kg:

max 10



Approvals:



Certificate NO.3-159-196/2017



## DRYER FOR SHOES SOUZ-10, SOUZ-10N\*\*

Dryer for shoes "Soyuz-10" was developed for drying wet and damp shoes.

### TECHNICAL PARAMETERS

The dimensions of the enclosure HxWxD, mm:	2020x620x160
The dimensions of the housing with the rods HxWxD, mm:	2150x620x380
The number of rods for shoes.PCs:	20
Weight, kg:	48
Supply voltage:	220B / 50Hz
Rated input, W:	
el. motor:	60
Heating element:	2000
germicidal lamp:	15,9
Type of germicidal lamp:	Philips TUV 15W
The lifespan of germicidal lamps, h	8000
Overheat protection:	yes
Drying modes:	40°C airing
Timer:	4 hours
	manual
Sound pressure level, dB:	<55
Fan productivity, m <sup>3</sup> /h:	360
The length of the electric power cord, m:	2,5

\*\* - N - made of stainless steel



Approvals:



Certificate NO.3-159-196/2017



## DRYER FOR SHOES SOUZ-20, SOUZ-20N\*\*

Dryer for shoes "Soyuz-20" was developed for drying wet and damp shoes for 20 pairs.

### TECHNICAL PARAMETERS

The dimensions of the enclosure HxWxD, mm:	2020x620x160
The dimensions of the housing with the rods HxWxD, mm:	2150x620x780
The number of rods for shoes.PCs:	40
Weight, kg:	88
Supply voltage:	220B / 50Hz
Rated input, W:	
el. motor:	60
Heating element:	2000
germicidal lamp:	15,9
Type of germicidal lamp:	Philips TUV 15W
The lifespan of germicidal lamps, h	8000
Overheat protection:	yes
Drying modes:	40°C airing
Timer:	4 hours
	manual
Sound pressure level, dB:	<55
Fan productivity, m <sup>3</sup> /h:	360
The length of the electric power cord, m:	2,5

\*\* - N - made of stainless steel



Approvals:



Certificate NO.3-159-196/2017



**CHOICE OF COLORS:**



**HOTBOX-2000**



**HOTBOX-2000/4**



**UNIVERSAL-2000**



**KIDBOX 5**



**RANGER 8**



**HOTSTORM**



**SOUZ-10**



**SOUZ-20**



Approvals:



Certificate NO.3-159-196/2017

